


Freudenberg Filtration Technologies, LP Safety Data Sheet

Date of issue: January 22 nd 2018		Date of revision:
1. Identification		
Product name	:	Viledon Booth Armor – Clear Washable
Product number(s)	:	73074542, 73074546
Company	:	Freudenberg Filtration Technologies, LP 2975 Pembroke Road, Hopkinsville, KY 42240 USA
Telephone	:	+1 (270) 887-5164
Telefax	:	+1 (270) 632-4847
e-Mail address	:	viledon@freudenberg-filter.com
Emergency telephone	:	+1 (800) 424-9300 (Chemtrec)
2. Hazard Identification		
Classification		Skin Sensitizer: Category 1A;
Label elements		WARNING
		
Hazard statements		May cause an allergic skin reaction (H317)
Precautionary statements		
Prevention		Avoid breathing dust/fume/gas/mist/vapors/spray (P261) Wear Protective gloves/protective clothing/eye protection/face protection (P280)
Response		IF ON SKIN: Wash with plenty of soap and water. (P302 + P352) If skin irritation or rash occurs: Get medical advice/attention. (P333 + P313) If eye irritation persists: Get medical advice/attention. (P337 + P313) Wash contaminated clothing before reuse. (P363)
Storage/disposal		Keep container tightly closed (P233) Dispose of contents/container in accordance with applicable local/regional/national regulations. (P501)
WHMIS		This product is regulated as a hazardous material by the Canadian Controlled Product Regulations and is a controlled product under the Workplace Hazardous Materials Information System.
HMIS Ratings:		Health: 1 Fire: 0 Physical Hazard: 0 (Hazard Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe; * = Chronic hazard)
3. Composition / information on ingredients		
Substance: This material does not meet the criteria of a substance.		
Ingredient	CAS #	% by weight
Water	7732-18-5	80 – 90
Viny acetate-vinyl alcohol polymer	25213-24-5	5 – 15
Polyethylene Glycol	25322-68-3	1 – 5
The exact percentage of this composition has been withheld as a trade secret.		

Freudenberg Filtration Technologies, LP Safety Data Sheet

4. First-aid measures	
General advice	: No specific measure to be taken
Inhalation	: Remove person to fresh air. If you feel unwell, get medical attention.
Skin contact	: Wash with soap and water. If signs/symptoms develop, get medical attention.
Eye contact	: Rinse with water. If signs/symptoms develop, get medical attention.
Ingestion	: Rinse mouth. If you feel unwell, get medical attention.
Information for the doctor	: Not applicable.
5. Fire fighting measures	
Suitable extinguishing media	: Use a fire-fighting agent suitable for ordinary combustible material such as water or foam to extinguish.
Special hazards	: Closed containers exposed to heat from fire may build pressure and explode. Dried film of coating will burn when free from the substrate.
Hazardous decomposition or by-products during combustion	: Carbon monoxide, carbon dioxide
Protective equipment for fire fighters	: Use self-contained breathing apparatus
Further information	: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosion/rupture.
6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures	: Ventilate the area with fresh air. For a large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.
Environmental precautions	: Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.
Methods and material for containment and cleaning up	: Contain spill. Work from around the edges of the spill inward and cover with commercially available inorganic absorbent material. Mix in sufficient absorbent material until it appears dry. Shovel as much of the material as possible into a suitable container. Seal the container and dispose of as soon as possible. Clean up residue with detergent and water.
7. Handling and storage	
Handling	: For industrial use only. Avoid contact with skin and eyes. Wash thoroughly after handling. Use with adequate ventilation and avoid breathing vapors or mists of this product. Wash contaminated clothing before reuse.
Storage	: Keep containers closed and in a cool, well-ventilated area. Protect from sunlight. Store away from heat. Store away from acids and oxidizers. Material is freeze-thaw stable but best practice for any water-borne coating is to protect from freezing whenever possible.

Freudenberg Filtration Technologies, LP Safety Data Sheet

8. Expose controls and personal protection	
Occupational exposure limits	
Vinyl acetate-vinyl alcohol (25213-24-5) :	CMRG: TWA (respirable dust): 5mg/m3; TWA (total dust): 10mg/m3
Polyethylene Glycol (25322-68-3) :	AIHA WEEL: TWA Particulate: 10mg/m3;
	CMRG = Chemical Manufacturer's Recommended Guidelines AIHA = American Industrial Hygiene Association WEEL = Workplace Environmental Exposure Level TWA = Time-Weighted Average based on 8hr/day and 40hr/week
Engineering controls	: Provide adequate ventilation as needed to control concentrations of airborne contaminants below applicable exposure limits. If ventilation is not adequate, use respiratory protection equipment.
Personal protective equipment	
Respiratory protection	: An exposure assessment may be needed to decide if a respirator is required. If needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, use either a half-facepiece or full-facepiece air-purifying respirator suitable for particulates. Consult respirator manufacturer for suitability for a specific application.
Eye protection	: Safety glasses with eye shields are recommended.
Skin/hand protection	: Wear protective gloves with cuffs. Normal work clothing (long sleeves and pants) is recommended.
General safety and hygiene measures	
Measures	: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.
Environmental exposure	: Follow best practices for site management and disposal of waste. Avoid release to the environment.
9. Physical and chemical properties	
Physical form	: Liquid
Color	: Light amber
Odor	: Mild
Boiling point/Boiling range	: 212°F / 100°C
Freezing temperature	: 32°F / 0°C
Flash point	: > 200°F [Test method: Closed Cup]
Explosion hazard	: Not applicable
Density	: 1.03 g/ml
Specific gravity	: 1.03 g/ml [Water=1]
Weight per gallon	: ~ 8.6 lbs per gallon
pH	: 5 – 8
Viscosity	: 300 – 600 cps [Brookfield]
Percent volatile	: 86%
VOC	: 0.49% weight; 5 g/l [calculated]
VOC (less H2O & exempts)	: 42 g/l [calculated]
Solubility in water	: complete
Solubility (non-water)	: No data available
Vapor pressure	: No data available

Freudenberg Filtration Technologies, LP Safety Data Sheet

10. Stability and reactivity	
Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable
Possibility of hazardous reactions	: Hazardous polymerization will not occur
Conditions to avoid	: None identified
Incompatible materials	: Reactive metals, strong acids, strong oxidizing agents
Hazardous decomposition products	: None known. Refer to section 5 for hazardous decomposition products during combustion.
11. Toxicological information	
Signs and symptoms	: Based on component information, this material may produce the following health effects:
Inhalation	: Respiratory tract irritation: signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.
Skin contact	: Contact with skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): signs/symptoms may include redness, swelling, blistering, itching.
Eye contact	: Sprayed material may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.
Ingestion	: Gastro-intestinal irritation: signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.
Polyethylene Glycol Acute toxicity	: Dermal Rabbit LD50 > 20,000mg/kg Ingestion Rat LD50 > 10,000mg/kg
Vinyl acetate-vinyl alcohol Acute toxicity	: Ingestion Rat LD50 > 5,000mg/kg
Skin corrosion/irritation	: Rabbit Slight irritation
Serious eye damage/irritation	: Rabbit Slight irritation
Skin sensitization	: Guinea Pig Not sensitizing
Photosensitization	: Either no data are currently available or the data are not sufficient for classification.
Respiratory sensitization	: Either no data are currently available or the data are not sufficient for classification.
Germ cell mutagenicity	: Either no data are currently available or the data are not sufficient for classification.
Carcinogenicity	: Either no data are currently available or the data are not sufficient for classification.
Reproductive toxicity	: Either no data are currently available or the data are not sufficient for classification.
12. Ecological information	
Biodegradability	: Vinyl acetate-vinyl alcohol polymer has been reported to be substantially biodegraded in several test systems after a lag time for microbial acclimation. Almost 100% degradation of 30-day BOD with an acclimated culture can be reached. Polyethylene glycol is expected to be readily biodegradable.
Ecotoxicity-components Polyethylene Glycol	: Fish (Pimephales promelas) 96 hr LC50: > 87,209 mg/l Water flea 48 hr LC50: > 53,484 mg/l
Vinyl acetate-vinyl alcohol	: Fish (Pimephales promelas) 96 hr LC50: > 40,000 ppm Fish (Lepomis macrochirus) 96 hr LC50: > 10,000 mg/l

Freudenberg Filtration Technologies, LP Safety Data Sheet

13. Disposal considerations

Product : Avoid disposal. Completely utilize product, if possible. Dispose unused product and container in accordance with local, regional, national, and international regulations. Incinerate unused product in a permitted waste incineration facility. As a disposal alternative, dispose of waste product in a permitted industrial waste facility.

EPA Hazardous Waste Number (RCRA) : Not regulated

14. Transport information

Not classified as dangerous in the terms of transport regulations.

Transportation during cold weather: This product is freeze-thaw stable and will function properly if it is frozen and then thawed. However, whenever possible, minimize the number of freeze cycles to which the product is exposed during transportation.

15. Regulatory information

Chemical inventory (U.S.) : All components of this product are included on the TSCA Chemical Inventory or are not required to be listed on the TSCA Chemical Inventory.

Chemical inventory (Canada) : All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.

Component analysis : None of the product's components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

16. Other information

DISCLAIMER: For industrial use only. Reasonable care has been taken in the preparation of this information and is believed to be accurate as of the date issued. Seller does not suggest or guarantee that any hazards listed herein are the only ones which exist and makes no warranty of any kind, express or implied, concerning the safe use of this material in user's process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials.

SELLER MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether this product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.

The information contained herein is based on the present state of knowledge and does not therefore guarantee certain properties. The technical safety information sheet only describes the products in aspect to their safety requirements. Recipients of our products must take on responsibility for observing existing laws and regulations.